

Dated: 21.10.2016

NOTICE**Quotation No:**

Sealed quotations are invited for the supply of the materials specified in the schedule attached below/overleaf. The rates quoted should be for delivery of the articles at the place mentioned below the schedule. The necessary superscription, due date for the receipt of quotations, the date up to which the rates will have to remain firm for acceptance and the name and address of officer to whom the quotation is to be sent are noted below. Any quotation received after the time fixed on the due date is liable to be rejected. The maximum period required for delivery of the articles should also be mentioned. Quotations not stipulating period of firmness and with price variation clause and/or 'subject to prior sale' condition are liable to be rejected.

The prices quoted should be inclusive of all taxes, duties, cesses, etc. which are or may become payable by the contractor under existing or future law or rules of the country of origin/supply or delivery during the course of execution of the contract.

Special conditions, if any, printed on the quotation sheets of the tenders or attached with the tender will not be applicable to the contract unless they are expressly accepted in writing by the purchaser.

Superscription : D1/4193/16

Quotation No :

Due date and time for receipt of quotations : 15/11/16 1 pm

Date and Time for opening Quotation : 15/11/16 2 pm

Date up to which the rates are to remain firm for : 31/03/16
acceptance

Designation and address of Officer whom the : Principal

quotation is to be addressed Rajiv Gandhi Institute of Technology, Kottayam

Place:Kottayam

Date:21.10.2016

Details of items**Quantity**

1.

5

Place:Kottayam

Rajiv Gandhi Institute of Technology, Kottayam

Date:21.10.2016

1. Digital SMD Rework Station - Motherboard, Mobile, SMD Soldering and Repair ESD is a hot air rework station with 270 W heating power. Temperature range from 100°C to 450°C, air volume \geq 24L/min. ESD Features PID controlled closed loop of sensor, rapid heating, precise and stable temperature. Suitable for soldering and desoldering surface mounted with ICs, such as QFP, PLCC, SOP, BGA etc. Intelligent cooling system, deferred air delivery when unit is off, auto power off when temperature drops below 100°C. Low vibration, free noise. ESD protection. ESD Technical Specifications Power consumption 270 W Temperature range 100C-450C Air volume \geq 24L/min Pump type diaphragm