Specifications

Sl No.	Specifications	Qty
01	Air Hand Blower, 4.2m3 of air flow	01
02	Swaging tool, punch type set of size, for tube 4.7 to 16mm OD	03
03	Swaging tool, screw type ,with adapter set of size for tube 4.7 to 16mm OD	03
04	Bending spring external type, for copper tube 3 to 10 mm. Dia	05
05	Pipe cutter with built in reamer and space cutter, for copper tube .suitable for cutting copper tube 3 to 32mm	02
06	Pinch of tool Block type for copper tube 6 to18 mm dia 4 4	03
07	Capillary plug gauge 0.026" to 0.064" 16 16	04
08	Pinch of plier (Crimping plier) tool for 6-18 mm dia copper tube 2 2	03
09	Piercing plier for 6-18 mm copper tube with accessories and fittings 8 8	03
10	Piercing valves for 6-18 mm copper tube with accessories and fittings	03
11	Valve key- T, handle 4.7 & 6.4mm.sq.	03
12	Lapping plate 250x200 mm (Glass type)	05
13	Hole Punch for cutting gasket for cutting hole in gasket of size 4.7 to 16mm dia (hollow punch)	03
14	Serviceman thermometer in metal case(-30 to+30 Deg. C)	02
15	Blow- lamp Brass Burner with heavy duty tank capacity 2 pint 6 6	03
16	Fin Comb / Fin straightainer for straiting 8,10,12,14,16 fins/inch coils with handle	03
17	Two way manifold with gauges	02
18	Gas leak detector for halogen gas	01
19	Refrigerant cylinder capacity 2.5 Kg	02
20	Evacuating & refrigerant charging station comprising Rotary two stage vacuum pump and motor (with gas ballast & anti suck back) Manifold with gauges & valves and capable of pulling vacuum up to 50 microns of Hg and with provision of connecting to a micro level vacuum gaugeGraduated charging cylinder with provisions for temperature correction and all necessary isolating valves Evacuating & charging station as above but fitted with weighing scale (up to 2 kg. in lieu of (b) above and with accuracy of +/- 1gram, for charging hydrocarbons	01
21	Two stage rotary vacuum pump of capacity approx 60-100 L/min., capable of evacuating to 50 microns of Hg and fitted with gas ballast, anti suck back valve and single phase motor.	01
22	Digital Sling Psychometre	01
23	Components of car AC systems - wobble plate compressor with mounting brackets serpentine evaporator parallel flow condenser, hoses, tubes, receiver, expansion valve electrical components & wiring harness	01
24	1 ton capacity full Split AC kit with - Indoor, Outdoor and remote kit	01
25	All the Components of 165 litre capacity refrigerator including electrical components& wiring harness	01
26	1 ton capacity full Window AC kit	01
27	TIG ARC Welding machine - with argon cylinder filled with gas Single phase200 Amps with flow metre and TigTourch assembly and allassessories. Input voltage 230 V. Welding Current Range 5-200 A. Cooling Type- Forced Air cooling type. Suitable for all types of electrodes	01
28	Dry wall screw driver GSR(6-25)TE professional	01
29	Sabre saw GSA 1300 PCE professional	01
30	Hot air gun GHG 600-3 professional	01